

HYDROELECTRIC ROV CONFIGURATION

PRO 4 HY 300BASE

THE PRO 4 HY 300BASE Hydroelectric ROV

System has been specifically configured for Engineers and Service Managers to quickly and effectively perform a variety of basic underwater infrastructure inspection tasks. Getting into tight spaces or intakes is no problem as the maximum diameter of the VideoRay is no more than 12 inches (25.4 cm). The VideoRay can and will go places few other ROVs can access. The ROV operator will gain valuable insight into the integrity of the structure while noticing immediate payback on this essential investment.



SYSTEM COMPONENTS

- » Pro 4 ROV Submersible
- » Pro 4 Control Panel (monitor not included)
- » Standard Computer With 15-Inch Display
VideoRay Cockpit Control Software Included
- » Wireless Programmable Hand Controller
- » Plug and Play Modular Tether:
40m (130 ft) Neutrally Buoyant
- » Pelican 1620 Hard Case with Custom Packaging
- » Basic Tool Kit with Complete Ballast Set
- » Sunshade
- » Owners Manual
- » Three (3) Days of Open Enrollment Training for One Operator





GENERAL SYSTEM

Power Requirements	100-240 VAC
Total System Weight	41.5 kg (91.4 lb)
Cases	2 Watertight Rugged Pelican Cases
Owners Manual	Hard Copy & Online Digital
System Tool Kit	Basic Tool Kit and P4 Maintenance Kit
Communications Protocol	RS-485
Warranty	2 Year Limited

SUBMERSIBLE

Depth Rating	305 m (1,000 ft)
Size	37.5, 28.9 22.3 cm (14.75, 11.4, 8.75in)
Weight	6.1 kg (13.5 lb) [with Full Ballast Set]
Ballast	(No Tools Required) Ballast System with Complete Stainless Ballast Set

PROPULSION (4.2 Knots Maximum Speed)

Horizontal/Vertical	2 Brushless/1 Brushless Direct Drive/Geared 100 mm Propellers/65 mm Propeller
---------------------	---

CAMERA

Main	High Resolution - NTSC or PAL Format Color and B&W Wide Dynamic Range Digital Slow Shutter White Balance
Sensitivity	20+ Real Time Camera Settings Color Mode: .004 lux B&W Mode: .0001 lux
View Angle	90° Horizontal/140° Diagonal
Vertical Tilt	180° Control

LIGHTING

(2) LED Array with 32 Emitters 3,600 lumens	Beam Spread covers entire range of Main Camera
--	--

INTEGRATED SENSORS

3D-Tilt Compensated Compass	Leak Indicator	Volt Meter
Accelerometer	Water Temperature	Depth Sensor
MEMS Gyro	Internal Temperature	

CONTROL PANEL

Size	53, 43, 22 cm (21, 17, 8.5 in)
Weight	16 kg (35 lb)
Computer	Standard Computer with 15-inch High Resolution screen display
Software	Programmed with complete suite of VideoRay Cockpit Control software
Main Display	Available as an Upgrade on BASE Configurations
Controller	Wireless USB Programmable Hand Controller
Recording	Integrated Recording (.WMV, .AVI formats) One Button Hand-Controlled Video and Still Image Recording
Overlay	Date, Time, Depth, Heading, Customized Text, Logo
Video Out	Digital or Analog Composite

TETHER

Length	40 m (130 ft) total length, Plug and Play Tether: 8 mm diameter, 454 kg (1,000 lbs) breaking strength
Management	Available as an Upgrade on BASE Configurations

INTEGRATED ACCESSORIES

INQUIRE WITH AN AUTHORIZED SALES REPRESENTATIVE ABOUT ADDITIONAL AVAILABLE ACCESSORIES FOR THIS ROV SYSTEM

www.videoray.com

212 East High Street, Pottstown, PA 19464

+1 610 458 3000 sales@videoray.com

© 2013 VideoRay LLC, VideoRay is a Registered Trademark of VideoRay LLC