

Accessory Data Sheet Subsea Vehicle Battery

The **Mission Specialist Subsea Vehicle Battery** delivers power to the Mission Specialist vehicles without the need for a topside power source. When combined with the lightweight Expeditionary Splashproof Controller and Expeditionary Reel, the operator's location is no longer bound by the location of power outlets. Available with either Nickel Metal Hydride or Lithium, the Mission Specialist Subsea Vehicle Battery is the perfect accessory for missions that require the smallest topside footprint or where topside power is not available.

SPECIFICATIONS

Chemistry

Battery: NiMH or Lithium

Output Voltage

Nominal Regulated: 48VDC

Max Current

15A per battery

Nominal Capacity 235 W-hr per battery Depth Rating 305m or 1000m

(984.ft. or 3,280.8ft)

SIZE & WEIGHT - BATTERY POD

Length 561mm (22.08in.) Diameter 89mm (3.50in.)

Weight

305m 4kg(8.8lbs) per battery 1,000m 4.4kg(9.7lbs) per battery

Weight in Water

 305m
 0.8kg(1.76lbs) per battery

 1,000m
 1.2kg(2.64lbs) per battery

Case Watertight Transit Case

FEATURES

Piezo switch actuation Pressure safety enabled relief valve (5 psi) Secondary pressure relief (50 psi) Tool less mounting Smart diagnostics and monitoring External smart charger included



1000m NiMH Battery Part# 71380