



WWW.VIDEORAY.COM

ACCESSORY INFORMATION

TETHER

NEUTRAL BUOYANCY TETHER

GENERAL INFORMATION

CABLE 3 Pairs with 4 conductors
KEVLAR90.71 kg (200 lb)
FOAM POLY TAPE

CONDUCTORS

Tinned copper wire (varying gauges from 20-28)

JACKET

Yellow Polyurethane (PU)
Wall Thickness nominal .030 in
Outside Diameter nominal .420 in
*Max voltage in tether is 48 volts DC

NEGATIVE BUOYANCY TETHER

GENERAL INFORMATION

CABLE 3 Pairs with 4 conductors
KEVLAR90.71 kg (200 lb)
FOAM POLY TAPE

CONDUCTORS

Tinned copper wire (varying gauges from 20-28)

JACKET

Yellow Polyurethane (PU)
Wall Thickness nominal .030 in
Outside Diameter nominal .320 in
*Max voltage in tether is 48 volts DC

PROFESSIONAL PERFORMANCE TETHER

GENERAL INFORMATION

CABLE 3 PAIRS 28 AWG
2 PAIR 24 AWG
PU jKT

CONDUCTORS

Tinned copper wire (varying gauges from 20-28)

WIRE INSULATION

Thermoplastic Rubber Walls

JACKET

Yellow Polyurethane (PU)
Wall Thickness nominal .032 in
Outside Diameter nominal .320 in
*Max voltage in tether is 48 volts DC