

# Mission Specialist Ally Premium Package



PN: 74953

The Mission Specialist Ally Premium Package includes the Ally submersible and a comprehensive suite of advanced underwater equipment. It features a manipulator with a 90-degree vertical swing for enhanced vertical lifting capability, a DVL for precise station keeping, navigation and mission planning, and a Multibeam sonar for navigation in conditions where camera visibility is compromised. The package also provides the Workhorse Control Console as the central user interface, along with 100 meters of Performance Tether and a tether backpack for convenient transport.

#### MISSION SPECIALIST ALLY

**Depth Rating:** 300 m (984 ft)

Weight in Air: 15.8 kg (34.8 lb) W / Accessories

11.3 kg (25 lbs)

**Propulsion:** 2 Horizontal Thrusters: 16.8 kg (37 lbs),

4 Knots (Forward Thrust)

2 Vectored Thrusters: 9.5 kg (21 lbs,) 0.8 m/s

Lateral Thrust: 6.1 kg (13.5 lbs), 1 Knot

Lifting Capacity Camera:

Ultra 4k Smart Camera

NVIDIA Jetson Orin NX

12MP Resolution (4.7K)

Digital Pan, Tilt, and Zoom

#### **WORKHORSE CONTROL CONSOLE**

**Size & Weight:** 53 x 43 x 22 cm (21 x 17 x 8.5 in)

15.2 kg (33.6 lbs)

**Features:** Industrial Hand Controller

IP68 Water proof keyboard

HD High Bright Touch Screen Monitor

Line Isolation Monitor

**Power Input:** Universal Input 85-264, VAC 47-440 Hz

2.4 kW Max Power (chassis)

**Power Output:** 2.3 kW Max at 400V (90%) efficiency





### Blueprint Subsea Oculus Sonar M750d

**Dimensions:** 125 x 122 x 62 mm

(4.92 x 4.80 x 2.44 in)

**Weight in Air:** 980 g (2.16 lb) 360 g (0.79 lb)

**Operating** 

**Frequency:** 750 kHz / 1.2 MHz 120 m / 40 m

**Maximum Range:** 



## **DVL (Doppler Velocity Log)**

 Diameter:
 66 mm (2.6 in)


 Height:
 25 mm (1 inch)

 Weight in Air:
 170 g (0.38 lb)

 Weight in Water:
 105 g (0.24 lb)

**Maximum Bottom** 

**Lock Range:** 20 - 30 m (65.6 - 98.4 ft)



## **Reach Alpha Manipulator**

Rotation:  $0.6 \text{Nm} \mid 60^{\circ}/\text{s}$ Linear Force:  $600 \text{N} \mid 2.5 \text{mm/s}$ Weight in Air: 390 g (0.86)Weight in Water: 240 g (0.53)

Swing Arm Mount:

A minimum load of 3.18 kg (7 lbs) in

water weight is required for a complete

90 degree swing.



# 100 m Performance / PPT - Copper Tether

**Diameter:** 9 - 10 mm (0.35 - 0.39 in)

**Buoyancy:** Neutral

**Breaking Strength:** 635 kg (1,400 lb)

Recommended

Maximum Length: 400 m (1,312 ft)

Bandwidth: 60 Mbps (Up to 300 m)

Features: Comes with a tether back pack for easy

storage and transportation.

