

Expeditionary

TETHER REEL



The Expeditionary Tether Reel, used in conjunction with Mission Specialist Subsea Vehicle Batteries, provides unmatched mobility and a small operational footprint without sacrificing performance or mission range. No topside power source is necessary when operating in this configuration, allowing for unlimited ROV deployment options.

For use with Mission Specialist Thin Copper tether.

_Specifications

POWER	24VDC Output
OPERATING TEMP	-20°C – 60°C (-4°F – 140°F)
RATING	IP65
CASE	26.5 × 26.5 × 25.3 in (67.3 x 67.3 × 64.1 cm)
REEL	18.0 x 18.3 × 18.4 in (45.7 × 46.5 x 46.7 cm)
TOTAL WEIGHT	62.4 lbs (28.3 kg)
BATTERIES	2590 (2) Li-ion or NiMH



_Key Features

- > 500m of 4.4 mm Thin Copper tether with protective sheath
- > Removable manual crank handle
- > Level wind carriage
- > Battery state of charge display
- > Auxiliary shore power cable
- > Watertight/crushproof hard-sided case

_Connections

RJ45 ETHERNET	Socket
USB-A	Socket
TOPSIDE USBL	Impulse MCBH-5-MP
HMI	Fischer UltiMate 12-pin
COPPER TETHER	Socket 8-pin to ROV



VERSION 251001

AV – ph: 703.418.2828 – www.avinc.com // © 2025 AeroVironment, its product names and the AV logo are protected trademarks of AeroVironment, Inc. All other company, product names, logos, and brands are property of their respective owners and are for identification purposes only. Use of these names, logos, and brands does not imply endorsement. Screen images may be simulated. All specifications are subject to change. This data sheet consists of AeroVironment, Inc. general capabilities information that does not contain controlled technical data as defined within the International Traffic in Arms Regulations (ITAR) Part 120.10 or Export Administration Regulations (EAR) Part 734.7-11.

